MULTIMODAL ACCESS CONTROL



FACEAC 05 5" SCREEN MODEL



- LINUX 3.10
- MULTIMODALITY: FACE/PASSWORD/ID,IC CARD/QR
 CODE
- 5-INCHES LCD TOUCH SCREEN, RESOLUTION 1280*720
- DATA MANAGEMENT BY HARDWARE PLATFORM
- LOGS CAPACITY 500,000
- FACE VERIFICATION ACCURACY 99.7%
- FACE COMPARISON SPEED < 0.2 S/PEOPLE
- SUPPORT MULTI-LANGUAGES

Technical Specification

System	
CPU	1.2G Dual Core ARM CotexA-7
RAM	256 MB, DDR3
ROM	eMMC Flash 4GB
os	Linux

Capacity	
Face (Optional)	5,000 (50,000)
Fingerprint	-
Card (Optional)	5,000 (50,000)
Password (Optional)	5,000 (50,000)
Event	500,000

Interface		
Network	LAN	RJ45
	Wifi	Optional
Lock Output		Support
Exit Button		Support
Door Contact Input		Support
RS-485		-
Wiegand		26, 34/Input 1, Output 1
USB		USB 2.0
Speaker		Support
Power		1

Authentication		
Face Recognition Distance	0.5 - 2.5 m	
Face Recognition Accuracy	99.70%	
Face Regonition Duration	≤ 0.2 s	
Card Type	ID Card	
Password	Support	
QR Code	Support	

General	
Working Temperature	-10 °C to 45 °C
Working Humidity	20% RH to 90% RH
Dimensions	154 mm × 152 mm × 22 mm
Language	English, Spanish, Arabic, Thai, Farsi, Protuguese, French, Italian, Japan, Korea, etc
Power Supply	12V/2A

Display	
Screen	5-inch/Touch Screen
Resolution	1280 × 720 Pixels
Automatic Fill Light	Support

Function	
Mask Detection	Support
Face Anti-spoofing	Support
Attendance Software	Support
Management Software	Support